



JLN-2735S

SELF-ADHESIVE KRAFT PAPER TAPE

Physical Properties	Standard	Metric	Test Method	
Color	Natural			
Adhesive	Water-based Adhesive			
Backing	70 g/m ² Kraft Paper			
Total Thickness	5.5 mils	0.14 mm	ASTM D-3652	GB/T7125
Peel Adhesion 90°	22 oz/in	6 N/25mm	ASTM D-3330	GB/T2792
Holding Power	≥3 h	≥3 h	ASTM D-3654	GB/T4851
Tensile Strength	20 lbs/in	90 N/25mm	ASTM D-3759	GB/T7753
Elongation at Break	1.5-3%	1.5-3%	ASTM D-3759	GB/T7753
Service Tem.--Mini	23°F	-5°C	BC/BD-220SE	BC/BD-220SE
Service Tem.--Max	212°F	100°C	DHG-9055A	DHG-9055A

Description:

JLN-2735S Packaging Tape is a fast, reliable sealing, economical, pressure-sensitive and self-adhesive packaging kraft tape that improves the efficiency of your packaging line. And is less prone to theft.

Use Method:

Tear off the tape and use it to seal the top and bottom of the cardboard box. Suitable for all types of cardboard boxes.

Storage Condition:

It' s recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4°C to 26°C and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Shelf Life:

1 years from the date of shipment

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JL3 product. JL3 does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products.

JL3 strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JL3 assumes no responsibility for any damage or injury sustained as a result of the use of its products.

Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.

Tel:+86 596-728-0001

info@jl3tape.com

http://www.jl3tape.com

