



Bi-Directional Filament Tape

| Physical Properties | Standard | Metric | Test Method | |
|---------------------|------------------|------------|-------------|-------------|
| Reinforcement | Fiberglass | | | |
| Adhesive | Synthetic Rubber | | | |
| Backing | PET | | | |
| Color | Light Yellow | | | |
| Total Thickness | 7.9 mils | 0.20 mm | ASTM D-3652 | GB/T7125 |
| Peel Adhesion 90° | 137 oz/in | 38 N/25mm | ASTM D-3330 | GB/T2792 |
| Holding Power | ≥48h | ≥48h | ASTM D-3654 | GB/T4851 |
| Tensile strength | 72 lbs/in | 320 N/25mm | ASTM D-3759 | GB/T7753 |
| Elongation at Break | 3-5% | 3-5% | ASTM D-3759 | GB/T7753 |
| Service TemMini | 23 °F | -5℃ | BC/BD-220SE | BC/BD-220SE |
| Service TemMax | 158 °F | 70℃ | DHG-9055A | DHG-9055A |













Description:

JLW-306 Backed with PET film and reinforced with glass fiber. It's high strength bi-directional filament tape with very high viscosity; suitable for pipe strapping; general bundling; pallet fixing; sealing and bundling reinforced marine carton.

Performance Features:

JLW-306 is a light yellow and high strength bi-directional filament tape. Glass fiber contributes higher tensile strength and improved synthetic rubber delivers stronger adhesion; generating bi-directionally strengthened effect; high resistance to abrasion; impact resistance and high holding power.

Storage Condition:

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4°C to 26°C and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Shelf Life:

1 years from the date of shipment

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JL3 product. JL3 does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. JL3 strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JL3 assumes no responsibility for any damage or injury sustained as a result of the use of its products.

Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.

> Tel:+86 596-728-0001 info@jl3tape.com http://www.jl3tape.com