TECHNICAL SPECIFICATION



JLT-6614A

Mono-Directional Clean Removal Filament Tape

Physical Properties	Standard	Metric	Test Method		
Reinforcement	Chemcial Fiber				
Adhesive	Acrylic Pressure-Sensitive Adhesive				
Backing	PET				
Color	Clear				
Total Thickness	7.1 mils	0.18 mm	ASTM D-3652	GB/T7125	
Peel Adhesion 90°	47 oz/in	13 N/25mm	ASTM D-3330	GB/T2792	
Holding Power	≥48 h	≥48 h	ASTM D-3654	GB/T4851	
Tensile strength	191 lbs/in	850 N/25mm	ASTM D-3759	GB/T7753	
Elongation at Break	23±3%	23±3%	ASTM D-3759	GB/T7753	
Service TemMini	14°F	-10°C	BC/BD-220SE	BC/BD-220SE	
Service TemMax	212°F	100℃	DHG-9055A	DHG-9055A	













Description:

JLT-6614A Backed with PET film and reinforced with chemical fiber. It's high strength mono-directional filament tape with high viscosity and long-term holding power. Suitable for heavy objects trapping; pipe strapping; pallets fixing; reinforced marine carton packaging.

Performance Features:

JLT-6614A is a transparent and high strength filament tape. Chemical fiber contributes higher tensile strength and improved acrylic pressure-sensitive adhesive delivers stronger adhesion; high resistance to abrasion; impact resistance and high holding power.

Storage Condition:

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be $4^{\circ}\mathbb{C}$ to $26^{\circ}\mathbb{C}$ and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Shelf Life:

1 years from the date of shipment

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JL3 product. JL3 does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. JL3 strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JL3 assumes no responsibility for any damage or injury sustained as a result of the use of its products.

Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.

> Tel:+86 596-728-0001 info@jl3tape.com http://www.jl3tape.com